







MEZCLADORA

Datos tecnicos

	REF	V	Hz	RPM	W		 Ø MAX.				
RUBIMIX-9 SUPERTORQUE	26970	210-240	50/60	0-450 0-780	1800	M14	Ø 160 mm 6 5/16"	590 mm 23 1/12"	60 L 13 gl	6,3 kg 13 7/8 lb	LpA = 81 dB(A) KpA = 3 dB(A) LWA = 98,6 dB(A)
RUBIMIX-9 SUPERTORQUE UK	26971	110-120	50/60	0-450 0-780	1800	M14	Ø 160 mm 6 5/16"	590 mm 23 1/12"	60 L 13 gl	6,3 kg 13 7/8 lb	
RUBIMIX-9 SUPERTORQUE UK	26972	210-240	50/60	0-450 0-780	1800	M14	Ø 160 mm 6 5/16"	590 mm 23 1/12"	60 L 13 gl	6,3 kg 13 7/8 lb	
RUBIMIX-9 SUPERTORQUE USA + CHUCK	26973	110-120	50/60	0-450 0-780	1800	M14	Ø 160 mm 6 5/16"	590 mm 23 1/12"	60 L 13 gl	6,3 kg 13 7/8 lb	
RUBIMIX-9 SUPERTORQUE + CASE	26974	210-240	50/60	0-450 0-780	1800	M14	Ø 160 mm 6 5/16"	590 mm 23 1/12"	60 L 13 gl	6,3 kg 13 7/8 lb	
RUBIMIX-9 SUPERTORQUE + CHUCK	26975	210-240	50/60	0-450 0-780	1800	M14	Ø 160 mm 6 5/16"	590 mm 23 1/12"	60 L 13 gl	6,3 kg 13 7/8 lb	